



MAINTAINING YOUR SPA

It is recommended that the filter cartridge(s) be cleaned every 3-6 weeks or as needed. Replace the filter cartridge(s) every 1-2 years or when necessary. To maintain warranty protection, use only genuine Filter Cartridge replacements. To clean your filter cartridge(s) complete the following:

Step 1: Place the spa in Standby mode

Step 2: Remove FilterCap™



Step 3: Remove cartridge(s)



Step 4: Using a garden hose with a nozzle or other high-pressure device, clean cartridge(s). Work top to bottom on each pleat.

- To remove collected suntan lotions or body oils, soak cartridge(s) in warm water with a Filter Cleaner or detergent.
- To remove calcium deposits, soak cartridge(s) in a plastic container using a 1:10 ratio of Muriatic acid to water solution. Calcium deposits indicate a high spa pH, which should be corrected.



Step 5: Reinstall cartridge(s) and Filter Cap

Step 6: Press any button to reset the control system.

IMPORTANT: Using a brush to clean a filter cartridge could cause damage to the cartridge.

Light Bulb and LED Replacement

To replace a burned out or defective light bulb or LED, complete the following:

Step 1: Turn off the electrical power at the breaker box.

Step 2: Remove the equipment compartment door.

Step 3: Locate the back of the light fixture.

For standard light bulb replacement:

Step 4: Grasp the light bulb holder (located on the back of the light fixture) and twist counter-clockwise to release the light from the fixture.

Step 5: Remove the light bulb by pulling it straight out of the light bulb holder.

Step 6: Replace the light bulb and reinstall the light bulb holder.

For LED replacement:

Step 4: Insert a small standard screwdriver into the tabbed slot (see arrow).

Step 5: Carefully pry off the back light fixture cover.

Step 6: Remove the LED assembly by pulling it straight out. Replace the LED. Reinstall the back cover of light fixture.

For both lighting systems:

Step 7: Replace the equipment compartment door.

Step 8: Restore the electrical power supply.

NOTE: For alternate lighting systems, contact your authorized Spa dealer.

Ozone Purifier Replacement

On the front of the Ozone Purifier (optional) is the indicator light. To verify that the Ozone Purifier is working properly, check to ensure that the indicator light is glowing while the filter pump is running during a period when the pump has been activated automatically.

IMPORTANT: The indicator light will not be on when any jets button has been activated manually. The light will remain off for 30 minutes thereafter.

NOTE: If the indicator light does not turn on during automatic filter pump operation, contact your authorized Spa dealer for service.